



ENVIRONMENTAL PRODUCT DECLARATION


IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

Fiberputs B (several variants) Finja Betong



EPD HUB, HUB-1984

Published on 06.10.2024, last updated on 06.10.2024, valid until 06.10.2029.









GENERAL INFORMATION

MANUFACTURER

Manufacturer	Finja Betong
Address	Betongvägen 1
Contact details	info@finja.se
Website	www.finja.se

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 und ISO 14025
PCR	EPD Hub Core PCR Version 1.1, 5 Dec 2023
Sector	Construction product
Category of EPD	Third party verified EPD
Parent EPD number	-
Scope of the EPD	Cradle to gate with modules C1-C4, D
EPD author	Martin Varma
EPD verification	Unabhängige Verifizierung dieser EPD und der Daten gemäß ISO 14025: ☐ Interne Prüfung ☑ Externe Verifizierung
EPD verifier	Imane Uald lamkaddam, as an authorized verifier acting for EPD Hub Limited


The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	Fiberputs B (several variants)
Additional labels	Included product names: Fiberputs B and Fiberputs B lågalkalisk
Product reference	-
Place of production	Finja, Sweden
Period for data	2023
Averaging in EPD	Multiple products
Variation in GWP-fossil for A1-A3	minus 0%, plus 2% from average %

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 metric ton
Declared unit mass	1000 kg
GWP-fossil, A1-A3 (kgCO₂e)	1,90E+02
GWP-total, A1-A3 (kgCO₂e)	1,90E+02
Secondary material, inputs (%)	1.79
Secondary material, outputs (%)	80
Total energy use, A1-A3 (kWh)	662
Net freshwater use, A1-A3 (m³)	2.14







PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Finja is a Swedish family business whose journey began with a gravel pit acquired in 1957.

Since then, and with a large amount of knowledge, dedication and courage, you now have today's

company – one of the country's largest companies in the concrete industry.

PRODUCT DESCRIPTION

General purpose plastic reinforced rendering mortar, use on walls, ceilings, columns and partitions, inside and outside. Classification according to EN 998-1: GP-CS III-WO. Please see product specific information om www.finja.se to choose the right mortar for the application.

Further information can be found at www.finja.se.

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass %	Material origin					
Metals	-	-					
Minerals	97	Europe					
Fossil materials	3	Europe					
Bio-based materials	-	-					

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate


Biogenic carbon content in product, kg C	-
Biogenic carbon content in packaging, kg C	1.96

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 metric ton
Mass per declared unit	1000 kg
Functional unit	
Reference service life	100

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0.1% (1000 ppm).







PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Pro	duct st	tage		mbly age			U	se sta	ge			Ei	nd of l	ife stag	ge	Beyond the system boundaries				
A1	A2	А3	A4	A5	B1	B2	В3	В4	В5	В6	В7	C1	C2	С3	C4	D				
×	×	×	MND	MND	MND	MND	MND	MND	MND	MND	MND	×	×	×	×		×			
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling		

Modules not declared = MND. Modules not relevant = MNR

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

Cement and sand/gravel aggregate is mixed at the factory plant. The mix is placed in bags of various sizes, placed on pallets and located in the storage area before transport to the customers warehouse.

TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

When ordered from customer the product is loaded for transport. The transports are optimised for maximum possible usage of load capacity.

During installation material loss will occur, mainly when handling the product.

PRODUCT USE AND MAINTENANCE (B1-B7)

This EPD does not cover the use phase.


Air, soil, and water impacts during the use phase have not been studied.

PRODUCT END OF LIFE (C1-C4, D)

After service life demolition is made mechanically. 100% of the demolished material can be used as new aggregate. However, it is assumed that 80% will be recycled and 20% will be land fill as according to concrete templates. The demolition process consumes diesel fuel used by building machines for example, excavator equipped with hydraulic hammer.

The demolished masonry mortar is delivered to the closest waste treatment plant for crushing and sorting.


Demolished masonry mortar can be used as landfill or as aggregate in new concrete. There are benefits outside system boundaries.







MANUFACTURING PROCESS







LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	Allocated by mass or volume
Packaging material	Allocated by mass or volume
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

AVERAGES AND VARIABILITY

Type of average	Multiple products
Averaging method	Averaged by shares of total mass
Variation in GWP-fossil for A1-A3	minus 0%, plus 2% from average %

This EPD is a weighted average, using annual production volume för each product in proportion. It covers two rendering products produced at Finjas plant in Hässleholm. The product specific GWP-f interval is from 1,90+E2 to 1,93+E2 kg CO2-e per metric ton where the higher value is origin from low-alcaline cement.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.8, Plastics Europe, Federal LCA Commons and One Click LCA databases as sources of environmental data.






ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	С3	C4	D
GWP – total ¹⁾	kg CO₂e	1,50E+02	1,37E+01	2,65E+01	1,90E+02	2,29E+01	1,14E+01	MND	3,31E+00	4,69E+00	6,79E+00	1,70E+00	-3,81E+00						
GWP – fossil	kg CO₂e	1,50E+02	1,37E+01	2,65E+01	1,90E+02	2,29E+01	1,14E+01	MND	3,31E+00	4,69E+00	6,59E+00	1,65E+00	-3,80E+00						
GWP – biogenic	kg CO₂e	-2,46E-01	0,00E+00	0,00E+00	-2,46E-01	8,84E-03	1,06E-03	MND	0,00E+00	0,00E+00	1,97E-01	4,92E-02	0,00E+00						
GWP – LULUC	kg CO₂e	7,25E-02	5,34E-03	1,72E-02	9,51E-02	8,43E-03	5,63E-03	MND	3,30E-04	1,73E-03	5,17E-03	1,29E-03	-5,69E-04						
Ozone depletion pot.	kg CFC-11e	1,04E-05	3,17E-06	1,89E-06	1,55E-05	5,26E-06	1,18E-06	MND	7,07E-07	1,08E-06	1,35E-06	3,36E-07	-7,93E-07						
Acidification potential	mol H⁺e	4,24E-01	6,93E-02	9,66E-02	5,90E-01	9,68E-02	3,90E-02	MND	3,44E-02	1,99E-02	5,57E-02	1,39E-02	-3,89E-02						
EP-freshwater ²⁾	kg Pe	7,45E-03	1,08E-04	3,98E-04	7,96E-03	1,87E-04	4,21E-04	MND	1,10E-05	3,84E-05	1,73E-04	4,32E-05	-1,92E-05						
EP-marine	kg Ne	5,37E-02	1,91E-02	2,25E-02	9,53E-02	2,88E-02	7,83E-03	MND	1,52E-02	5,90E-03	2,07E-02	5,18E-03	-1,70E-02						
EP-terrestrial	mol Ne	1,00E+00	2,11E-01	2,48E-01	1,46E+00	3,17E-01	1,07E-01	MND	1,67E-01	6,51E-02	2,28E-01	5,70E-02	-1,87E-01						
POCP ("smog") ³)	kg NMVOCe	3,70E-01	6,63E-02	8,46E-02	5,21E-01	1,02E-01	3,63E-02	MND	4,59E-02	2,08E-02	6,36E-02	1,59E-02	-5,13E-02						
ADP-minerals & metals4)	kg Sbe	7,11E-04	3,19E-05	1,01E-04	8,44E-04	5,36E-05	4,72E-05	MND	1,68E-06	1,10E-05	2,18E-05	5,46E-06	-3,15E-06						
ADP-fossil resources	MJ	1,84E+03	2,06E+02	4,01E+02	2,45E+03	3,43E+02	1,50E+02	MND	4,45E+01	7,05E+01	1,13E+02	2,84E+01	-5,12E+01						
Water use ⁵⁾	m³e depr.	6,95E+01	9,19E-01	2,83E+01	9,87E+01	1,54E+00	5,11E+00	MND	1,20E-01	3,15E-01	1,08E+00	2,71E-01	-5,34E+00						

¹⁾ GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.







ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF


Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	В5	В6	В7	C1	C2	С3	C4	D
Particulate matter	Incidence	3,73E-06	1,54E-06	1,22E-06	6,49E-06	2,63E-06	9,33E-07	MND	9,22E-07	5,41E-07	7,14E-06	1,79E-06	-1,03E-06						
Ionizing radiation ⁶⁾	kBq 11235e	4,52E+03	9,91E-01	1,08E+01	4,54E+03	1,64E+00	2,27E+02	MND	2,05E-01	3,36E-01	1,12E+00	2,79E-01	-2,51E-01						
Ecotoxicity (freshwater)	CTUe	1,43E+03	1,82E+02	3,28E+02	1,94E+03	3,09E+02	1,21E+02	MND	2,68E+01	6,34E+01	8,00E+01	2,00E+01	-3,25E+01						
Human toxicity, cancer	CTUh	1,37E-07	4,76E-09	1,93E-08	1,61E-07	7,59E-09	8,80E-09	MND	1,03E-09	1,56E-09	3,52E-09	8,79E-10	-1,47E-09						
Human tox. non-cancer	CTUh	2,00E-06	1,79E-07	1,81E-07	2,36E-06	3,06E-07	1,41E-07	MND	1,94E-08	6,27E-08	6,73E-08	1,68E-08	-2,37E-08						
SQP ⁷⁾	-	3,45E+02	2,31E+02	9,81E+02	1,56E+03	3,96E+02	1,09E+02	MND	5,79E+00	8,12E+01	1,17E+02	2,91E+01	-1,96E+03						

⁶⁾ EN 15804+A2 disclaimer for lonizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	С3	C4	D
Renew. PER as energy ⁸⁾	MJ	1,07E+02	2,35E+00	9,77E+01	2,07E+02	3,87E+00	1,10E+01	MND	2,54E-01	7,94E-01	6,23E+00	1,56E+00	-5,41E-01						
Renew. PER as material	MJ	1,53E+00	0,00E+00	0,00E+00	1,53E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	-1,53E+00	0,00E+00	0,00E+00						
Total use of renew. PER	MJ	1,08E+02	2,35E+00	9,77E+01	2,08E+02	3,87E+00	1,10E+01	MND	2,54E-01	7,94E-01	4,69E+00	1,56E+00	-5,41E-01						
Non-re. PER as energy	MJ	1,28E+03	2,06E+02	5,02E+02	1,99E+03	3,43E+02	1,28E+02	MND	4,45E+01	7,05E+01	1,13E+02	2,84E+01	-5,12E+01						
Non-re. PER as material	MJ	6,34E+02	0,00E+00	0,00E+00	6,34E+02	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	-5,58E+02	0,00E+00	0,00E+00						
Total use of non-re. PER	MJ	1,91E+03	2,06E+02	5,02E+02	2,62E+03	3,43E+02	1,28E+02	MND	4,45E+01	7,05E+01	-4,44E+02	2,84E+01	-5,12E+01						
Secondary materials	kg	1,79E+01	5,91E-02	2,58E-01	1,82E+01	9,53E-02	9,20E-01	MND	1,74E-02	1,96E-02	4,09E-02	1,02E-02	-2,58E-02						
Renew. secondary fuels	MJ	7,01E+01	5,59E-04	1,74E+00	7,19E+01	9,62E-04	3,59E+00	MND	5,70E-05	1,97E-04	5,94E-04	1,49E-04	-7,16E-04						
Non-ren. secondary fuels	MJ	1,15E+02	0,00E+00	0,00E+00	1,15E+02	0,00E+00	5,74E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Use of net fresh water	m³	1,70E+00	2,64E-02	4,09E-01	2,14E+00	4,45E-02	1,14E-01	MND	2,70E-03	9,13E-03	6,31E-02	1,58E-02	-1,64E-01						

⁸⁾ PER = Primary energy resources.







END OF LIFE – WASTE


Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Hazardous waste	kg	2,97E+00	2,68E-01	8,20E-01	4,05E+00	4,55E-01	2,50E-01	MND	5,96E-02	9,34E-02	2,46E-01	6,15E-02	-8,55E-02						
Non-hazardous waste	kg	4,94E+02	4,34E+00	1,69E+01	5,15E+02	7,48E+00	3,55E+01	MND	4,19E-01	1,54E+00	1,47E+02	3,67E+01	-7,68E-01						
Radioactive waste	kg	2,49E-02	1,39E-03	4,27E-03	3,06E-02	2,30E-03	1,72E-03	MND	3,13E-04	4,71E-04	7,65E-04	1,91E-04	-3,55E-04						

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	СЗ	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Materials for recycling	kg	4,38E-01	0,00E+00	8,20E-02	5,20E-01	0,00E+00	2,60E-02	MND	1,00E+01	0,00E+00	8,00E+02	0,00E+00	0,00E+00						
Materials for energy rec	kg	0,00E+00	0,00E+00	4,93E-02	4,93E-02	0,00E+00	2,47E-03	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Global Warming Pot.	kg CO₂e	7,11E+01	1,36E+01	2,59E+01	1,11E+02	2,26E+01	7,36E+00	MND	3,27E+00	4,64E+00	6,51E+00	1,63E+00	-3,76E+00						
Ozone depletion Pot.	kg CFC-11e	7,40E-06	2,51E-06	1,56E-06	1,15E-05	4,17E-06	8,93E-07	MND	5,60E-07	8,55E-07	1,07E-06	2,68E-07	-6,29E-07						
Acidification	kg SO₂e	2,46E-01	5,45E-02	7,75E-02	3,78E-01	7,52E-02	2,61E-02	MND	2,45E-02	1,54E-02	4,14E-02	1,04E-02	-2,78E-02						
Eutrophication	kg PO ₄ ³e	2,05E-01	1,08E-02	2,26E-02	2,38E-01	1,71E-02	1,40E-02	MND	5,69E-03	3,52E-03	1,37E-02	3,43E-03	-6,62E-03						
POCP ("smog")	kg C ₂ H ₄ e	5,13E-02	2,02E-03	6,45E-03	5,98E-02	2,94E-03	3,25E-03	MND	5,36E-04	6,03E-04	1,26E-03	3,14E-04	-6,31E-04						
ADP-elements	kg Sbe	6,92E-04	3,10E-05	1,23E-04	8,46E-04	5,19E-05	4,72E-05	MND	1,65E-06	1,07E-05	2,15E-05	5,38E-06	-3,10E-06						
ADP-fossil	MJ	1,58E+03	2,06E+02	6,11E+02	2,40E+03	3,43E+02	1,48E+02	MND	4,45E+01	7,05E+01	1,13E+02	2,83E+01	-5,12E+01						







ENVIRONMENTAL IMPACTS – GWP-GHG - THE INTERNATIONAL EPD SYSTEM

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
GWP-GHG ⁹⁾	kg CO₂e	1,50E+02	1,37E+01	2,65E+01	1,90E+02	2,29E+01	1,14E+01	MND	3,31E+00	4,69E+00	6,59E+00	1,65E+00	-3,80E+00						

⁹⁾ This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product as defined by IPCC AR 5 (IPCC 2013). In addition, the characterisation factors for the flows - CH4 fossil, CH4 biogenic and Dinitrogen monoxide - were updated in line with the guidance of IES PCR 1.2.5 Annex 1. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO2 is set to zero.





VERIFICATION STATEMENT

VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Imane Uald lamkaddam, as an authorized verifier acting for EPD Hub Limited 06.10.2024



