

General information

Product:

PAROC FI Produced Stone Wool Thermal Insulation

Program Operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Tlf: +47 23 08 80 00
e-mail: post@epd-norge.no

Declaration Number:

0202120272

This declaration is based on Product

Category Rules:

CEN Standard EN 15804+A2 serves as core PCR. NPCR PART A Construction Products and Services NPCR 012 Part B for Thermal Insulation Products.

Statements:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer, life cycle assessment data and evidence.

Declared unit:

1 m² of stone wool with a thermal resistance (R) of 1 m²K/W.

Declared unit with option:

Functional unit:

1 m² of stone wool with thermal resistance (R) of 1 m²K/W. 1 m² of the reference product, PAROC eXtra, at R=1 is at a weight of 1,03 kg. The impact excludes any lamination.

Verification:

Independent verification of the declaration and data, according to ISO14025:2010

internal



external

Martin Erlandsson, IVL

Independent verifier approved by EPD Norway

Owner of the declaration:

Paroc Group Oy
Contact person: Emelia Samuelsson
Phone: +358 46 876 8000
e-mail: InsulationEurope.Sustainability@owenscorning.com

Manufacturer:

Paroc Group Oy
FI-00181, Helsinki, Finland
Phone: +358 46 876 8000
e-mail: InsulationEurope.Sustainability@owenscorning.com

Place of production:

Parainen, Finland

Management system:

ISO 9001 and ISO 14001

Organisation no:

887294852

Issue date:

0202120272

Valid to:

0202120272

Year of study:

2021

Comparability:

EPDs from other programmes than EPD Norway may not be comparable.

The EPD has been worked out by:

Emelia Samuelsson, Owens Corning

Emelia Samuelsson



Approved

Manager of EPD Norway

Product

Product description:

PAROC® stone wool insulation is naturally non-combustible and durable. It is made of natural stone (~98%) and air (~2%). As stone wools thermal performance is based on static air, insulation products keep their energy saving abilities and dimensions in different temperature and moisture conditions during the life cycle of a building.

The products covered by this declaration are PAROC stone wool thermal insulation products manufactured in Parainen, Finland using a low carbon melting technology, based on an electric melter with renewable electricity.

Product specification:

The average composition used for this EPD is calculated based on line consumption figures for raw materials. The raw materials are mainly natural stones and resin binder.

Materials	%
Stone Wool Fiber	>94
Binder (phenol-formaldehyde-urea-copolymer)	>5
Dustbinding (mineral oil)	<1

Technical data:

For the products covered by this EPD, the performance data are in accordance with the declaration of performance with respect to its essential characteristics according to EN 13162:2012+A1:2015, "Thermal insulation products for buildings – Factory made mineral wool (MW) products – Specification."

- Thermal conductivity: 0,032-0,050 W/mK, EN 12939 and EN 12667
- Fire class: A1, EN 13501-1:2007+A1:2009

Complete technical specifications can be found on www.paroc.com

Market:

This EPD is intended for the markets that receives PAROC products from the factory in Parainen, Finland. Those markets are mainly Finland, Sweden and Norway.

Reference service life, product:

The reference service life of PAROC products is equal to the reference service life of the building. For the purpose of this EPD the reference service life is considered to be minimum 60 years, which is usually the assumption about the lifetime of the building where this is installed.

Reference service life, building:

The reference service life of a building is set to 60 years in this EPD.

LCA: Calculation rules

Declared unit:

The declared unit refers to 1 m² of PAROC eXtra with a thermal resistance (R) of 1 m²K/W, thickness of 36 mm and weight of 1,03 kg.

The specific product, PAROC eXtra, is a stone wool slab with a density of 28,7 kg/m³ and thickness of 100 mm.

The impact indicators for another product can be calculated by multiplying the results of the EPD with the respective scaling factor for the products covered by this EPD. A table with the products available in the scaling table and their respective scaling factors is provided within the 'Additional technical information' section.

Data quality:

All primary data are collected line specific, based on the financial year 2021. The production data from Parainen involves a production line with an electric melter and renewable electricity.

The background data has been taken from the latest available GaBi database (/GaBi TS) CUP 2022.2. The requirements for data quality and background data correspond to the specifications of EN 15804+A2. The process data and the used background data are consistent.

The data quality can be qualified as good.

Allocation:

The allocation correspond to the specifications of EN 15804+A2. Allocation and other methodological choices are made consistently throughout the model. As a worst-case approach, price allocation is considered for the plant.




Figure 1. Schematic representation of the LCA system boundaries for the production module (A1-A3)




Figure 2. Schematic representation of the LCA system boundaries for the construction process stage (A4-A5)




Figure 3. Schematic representation of the LCA system boundaries for the End-of-life stage (C1-C4)




Figure 4. Schematic representation of the LCA system boundaries for the benefits and loads beyond the product system boundary in module D

System boundary:

The system boundary of the EPD follows the modular structure defined by EN15804+A2. The flowchart above represents the system boundaries for the product, construction process, end-of-life and benefits (D). The use stage (B1-B7) relating to the building site is not included in this study, as there are no activities and no significant environmental impact in the use stage.

Cut-off criteria:

All data from the production data acquisition has been considered, i. e. all basic materials used per formulation, utilized thermal energy, internal fuel consumption and electric power consumption, direct production waste, and all emission measurements available. All material and energy flows, except paper for labels in packaging, with a proportion of less than 1% have been considered. The neglected flow (paper label for packaging) does not exceed 1% of the impact categories. Machines and facilities required during production are neglected.

The declared unit of stone wool is without any coating.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD. There are no maintenance (B2), repair (B3), replacements (B4) or refurbishments (B5) required during the use of PAROC stone wool thermal insulation products in standard conditions. They do not require energy (B6) or water (B7) during their operational life. No significant emissions to the indoor environment occur in module (B1). Therefore, modules B1-B7 are not relevant for this EPD.

Transport from production place to assembly/user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance KM	Fuel/Energy consumption (l/t.km)	value (l/t for total distance)
Truck	30	Truck, Euro 5, 27 t payload	306	0,006	1,84

The A4 distance is calculated as average distance for the Finnish market.

Assembly (A5)

	Unit	Value
Auxiliary	kg	0,00
Water consumption	m ³	0,00
Electricity consumption	kWh	0,00
Other energy carriers	MJ	0,00
Material loss	kg	0,02
Output materials from waste treatment	kg	0,06
Dust in the air	kg	0,00

The installation in general takes place manually. Thus, machines or energy expenditures are not taken into account. Most products are self-supporting and do not need support. Installation losses have been accounted for 2% as a conservative approach. Within module A5 a site related packaging waste processing is included in the LCA. It is assumed that packaging material as leftover of the installed product is for 100% collected and incinerated.

End of Life (C1, C3, C4)

	Unit	Value
Hazardous waste disposed	kg	0,00
Collected as mixed construction waste	kg	0,00
Reuse	kg	0,00
Recycling	kg	0,00
Energy recovery	kg	0,00
To landfill	kg	1

Although mineral wool products from Paroc can be recycled, they are estimated as being 100% landfilled after the use phase as the most conservative approach. Post-consumer recycling scenarios are not considered within this study, however in Finland, Sweden and Norway a REWOOL take back system is well-established for stone wool waste.

Transport to waste processing (C2)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance KM	Fuel/Energy consumption (l/t.km)	value (l/t for total distance)
Truck	50	Truck, Euro 5, 27 t payload	50	0,006	0,30

The distance represents an average distance to landfill, the stone wool is in general not transported alone to landfill, therefore a load factor of 50% is considered in this case.

Benefits and loads beyond the system boundaries (D)

Benefits are considered in module D for the thermal and electrical energy, generated in module A5, due to thermal treatment of packaging waste (polyethylene film and wooden pallets) after installation.

Additional technical information

Below a list of products covered by this EPD and their scaling factors. The scaling factor can be used to estimate the environmental performance indicators for the specific products of 1 m² when R=1. The environmental performance solely refer to the stone wool, and thus do not include the environmental performance of any potential coatings. Due to this fact, the variation is less than 10% by reason of the density, lambda and binder. The scaling calculation shall be done as follows:

Reference product environmental impact per m² (0,289) x scaling factor of specific product (1,00)

Product Group	Product Name	Unit	Value
Flexible Slabs and Mats	PAROC eXtra (thickness >50-225 mm, lambda 0,036, average density 28,7 kg/m ³)	1 m ²	1,00
Flexible Slabs and Mats	PAROC eXtra (thickness 30 mm, lambda 0,036, average density 40 kg/m ³)	1 m ²	1,39
Flexible Slabs and Mats	PAROC eXtra (thickness 40-50 mm, lambda 0,036, average density 32 kg/m ³)	1 m ²	1,11
Flexible Slabs and Mats	PAROC eXtra pro (thickness 50-200 mm, lambda 0,033, average density 44 kg/m ³)	1 m ²	1,41
Flexible Slabs and Mats	PAROC eXtra F (thickness 50-225 mm, lambda 0,036, average density 31 kg/m ³)	1 m ²	1,08
Facade	PAROC Cortex one (thickness 100-220 mm, lambda 0,033, average density 52,5 kg/m ³)	1 m ²	1,68
Facade	PAROC COS 5 (gt) (ggt) (thickness 30 mm, lambda 0,035, average density 81,5 kg/m ³)	1 m ²	2,76
Facade	PAROC COS 5 (thickness 50-70 mm, lambda 0,035, average density 66,5 kg/m ³)	1 m ²	2,25
Facade	PAROC COS 5 (ggt) (thickness 100-240 mm, lambda 0,035, average density 55 kg/m ³)	1 m ²	1,86
Facade	PAROC COS 10 (ggt) (thickness 80-240 mm, lambda 0,035, average density 65 kg/m ³)	1 m ²	2,20
Facade	PAROC Cortex pro (thickness 40-70 mm, lambda 0,032, average density 80 kg/m ³)	1 m ²	2,48
Facade	PAROC Cortex (b) (thickness 30 mm, lambda 0,033, average density 110 kg/m ³)	1 m ²	3,51

Facade	PAROC Linio 80 (thickness 180-270 mm, lambda 0,040, average density 81 kg/m ³)	1 m ²	3,14
Facade	PAROC Linio 15 (thickness 70-200 mm, lambda 0,037, average density 99 kg/m ³)	1 m ²	3,55
Facade	PAROC Linio 15 (thickness 20-<30 mm, lambda 0,037, average density 157 kg/m ³)	1 m ²	5,62
Facade	PAROC Linio 15 (thickness 50-120 mm, lambda 0,037, average density 104 kg/m ³)	1 m ²	3,71
Facade	PAROC Linio 15 (thickness 30 mm, lambda 0,037, average density 153 kg/m ³)	1 m ²	5,48
Facade	PAROC WAS 25t (thickness 30-50 mm, lambda 0,033, average density 85 kg/m ³)	1 m ²	2,71
Facade	PAROC WAB 10 (thickness 17-50 mm, lambda 0,036, average density 148 kg/m ³)	1 m ²	5,14
Facade	PAROC WAB 10t (thickness 13 mm, lambda 0,036, average density 180 kg/m ³)	1 m ²	6,27
Facade	PAROC Fatio plus (thickness 50-220 mm, lambda 0,033, average density 75,5 kg/m ³)	1 m ²	2,41
Facade	PAROC Fatio Standard (thickness 100-240 mm, lambda 0,035, average density 55 kg/m ³)	1 m ²	1,86
Facade	PAROC Fatio Standard (thickness 50 mm, lambda 0,035, average density 66,5 kg/m ³)	1 m ²	2,25
Facade	PAROC PreCast ggt (thickness 205-245 mm, lambda 0,034, average density 62 kg/m ³)	1 m ²	2,04
Facade	PAROC Trio (thickness 185-250 mm, lambda 0,033, average density 52 kg/m ³)	1 m ²	1,66
Roofs	PAROC ROL 30 (thickness 200-450 mm, lambda 0,038, average density 63 kg/m ³)	1 m ²	2,32
Roofs	PAROC ROL 50 (thickness 240-375 mm, lambda 0,039, average density 75 kg/m ³)	1 m ²	2,83
Roofs	PAROC ROS 30 (g) (thickness >100-200 mm, lambda 0,036, average density 100 kg/m ³)	1 m ²	3,48
Roofs	PAROC ROS 30 (g) (gt) (t) (thickness 40-100 mm, lambda 0,036, average density 106 kg/m ³)	1 m ²	3,68
Roofs	PAROC ROS 40 (g) (gt) (t) (thickness 40-190 mm, lambda 0,037, average density 115 kg/m ³)	1 m ²	4,12
Roofs	PAROC ROS 50 (g) (gt) (t) (thickness >100-190 mm, lambda 0,038, average density 125 kg/m ³)	1 m ²	4,60
Roofs	PAROC ROS 50 (g) (gt) (t) (thickness 50-100 mm, lambda 0,038, average density 131 kg/m ³)	1 m ²	4,82
Roofs	PAROC ROS 60 (t) (thickness 35-100 mm, lambda 0,039, average density 150 kg/m ³)	1 m ²	5,66
Roofs	PAROC ROB 50 (t) (thickness 30 mm, lambda 0,037, average density 146 kg/m ³)	1 m ²	5,23
Roofs	PAROC ROB 60 (gt) (t) (thickness 30 mm, lambda 0,038, average density 174 kg/m ³)	1 m ²	6,40
Roofs	PAROC ROB 80 (g) (gt) (t) (thickness 20-30 mm, lambda 0,038, average density 192 kg/m ³)	1 m ²	7,06
Roofs	PAROC ROB 100 (gtrl) (thickness 30 mm, lambda 0,038, average density 215 kg/m ³)	1 m ²	7,91
Special Applications	PAROC SSB 1 (thickness 30-50 mm, lambda 0,035, average density 120 kg/m ³)	1 m ²	4,07
Special Applications	PAROC SSB 2 (t) (thickness 30-50 mm, lambda 0,037, average density 174 kg/m ³)	1 m ²	6,21
Special Applications	PAROC FPS 14 (thickness 50 mm, lambda 0,037, average density 140 kg/m ³)	1 m ²	5,01
Special Applications	PAROC FPS 17 (thickness 20-60 mm, lambda 0,038, average density 170 kg/m ³)	1 m ²	6,25
Special Applications	PAROC FireSAFE RF30 (thickness 30-50 mm, lambda 0,037, average density 112 kg/m ³)	1 m ²	4,01
Special Applications	PAROC FireSAFE VF10 (thickness 30 mm, lambda 0,035, average density 90 kg/m ³)	1 m ²	3,05
Special Applications	PAROC FireSAFE VF30 (thickness 50 mm, lambda 0,035, average density 170 kg/m ³)	1 m ²	5,76
Special Applications	PAROC FireSAFE RO30 (thickness 30-50 mm, lambda 0,035, average density 177 kg/m ³)	1 m ²	5,98

LCA: Results

The system boundary of the EPD follows the modular structure defined by EN15804+A2. The table identifies the modules included in this study. The use stage (B1-B7) relating to the building site is not included in this study, as there are no activities and no significant environmental impact in the use stage.

System boundaries (X=included, MND= module not declared, MNR=module not relevant)

Product stage			Assembly stage		Use stage							End of life stage				Benefits & loads beyond system boundary
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MNR	MNR	MNR	MNR	MNR	MNR	MNR	X	X	X	X	X

Core environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO2 eq.	2,89E-01	6,56E-03	1,17E-01	1,07E-02	3,24E-03	0	1,40E-02	-4,64E-02
GWP-fossil	kg CO2 eq.	3,50E-01	6,51E-03	5,51E-02	1,06E-02	3,20E-03	0	1,39E-02	-4,61E-02
GWP-biogenic	kg CO2 eq.	-6,12E-02	1,47E-05	6,15E-02	9,53E-05	2,04E-05	0	5,38E-05	-2,36E-04
GWP-LULUC	kg CO2 eq.	1,14E-04	3,66E-05	3,23E-06	2,24E-06	1,77E-05	0	2,56E-05	-5,08E-06
ODP	kg CFC11 eq.	3,32E-13	3,93E-16	1,47E-14	1,55E-13	1,90E-16	0	3,26E-14	-3,13E-13
AP	mol H ⁺ eq.	4,56E-03	5,04E-06	1,07E-04	2,32E-05	1,08E-05	0	9,84E-05	-6,08E-05
EP-freshwater	kg P eq.	2,19E-07	1,96E-08	6,16E-09	3,09E-08	9,47E-09	0	2,35E-08	-6,36E-08
EP-marine	kg N eq.	3,35E-04	1,34E-06	1,12E-05	5,21E-06	5,02E-06	0	2,52E-05	-1,65E-05
EP-terrestrial	mol N eq.	1,58E-02	1,65E-05	3,89E-04	5,47E-05	5,60E-05	0	2,76E-04	-1,76E-04
POCP	kg NMVO C eq.	9,00E-04	4,32E-06	2,99E-05	1,41E-05	9,76E-06	0	7,64E-05	-4,61E-05
ADP-M&M	kg Sb eq.	7,08E-08	5,48E-10	1,56E-09	2,88E-09	2,65E-10	0	1,42E-09	-6,97E-09
ADP-fossil	MJ	3,43E+00	8,76E-02	7,25E-02	1,92E-01	4,24E-02	0	1,82E-01	-7,84E-01
WDP	m ³	4,93E-02	5,88E-05	1,30E-02	2,41E-03	2,85E-05	0	1,52E-03	-4,93E-03

GWP-total: Global Warming Potential; **GWP-fossil:** Global Warming Potential fossil fuels; **GWP-biogenic:** Global Warming Potential biogenic; **GWP-LULUC:** Global Warming Potential land use and land use change; **ODP:** Depletion potential of the stratospheric ozone layer; **AP:** Acidification potential, Accumulated Exceedance; **EP-freshwater:** Eutrophication potential, fraction of nutrients reaching freshwater end compartment; See “additional requirements” for indicator given as PO4 eq. **EP-marine:** Eutrophication potential, fraction of nutrients reaching freshwater end compartment; **EP-terrestrial:** Eutrophication potential, Accumulated Exceedance; **POCP:** Formation potential of tropospheric ozone; **ADP-M&M:** Abiotic depletion potential for non-fossil resources (minerals and metals); **ADP-fossil:** Abiotic depletion potential for fossil resources; **WDP:** Water deprivation potential, deprivation weighted water consumption

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	8,40E-08	5,39E-11	1,61E-09	1,93E-10	5,73E-11	0	1,21E-09	-5,03E-10
IRP	kBq U235 eq.	7,28E-03	1,59E-05	3,93E-04	5,20E-03	7,67E-06	0	2,25E-04	-1,05E-02
ETP-fw	CTUe	1,68E+00	6,08E-02	3,43E-02	8,41E-02	2,94E-02	0	1,02E-01	-1,73E-01
HTP-c	CTUh	3,19E-09	1,23E-12	6,45E-11	2,42E-12	5,93E-13	0	1,55E-11	-7,92E-12
HTP-nc	CTUh	2,49E-09	6,75E-11	9,91E-11	8,90E-11	3,55E-11	0	1,72E-09	-3,07E-10
SQP	Dimensionless	9,39E+00	3,02E-02	1,25E-02	6,92E-02	1,46E-02	0	3,78E-02	-1,40E-01

PM: Particulate matter emissions; **IRP:** Ionising radiation, human health; **ETP-fw:** Ecotoxicity (freshwater); **ETP-c:** Human toxicity, cancer effects; **HTP-nc:** Human toxicity, non-cancer effects; **SQP:** Land use related impacts / soil quality

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

Classification of disclaimers to the declaration of core and additional environmental impact indicators

ILCD classification	Indicator	Disclaimer
ILCD type / level 1	Global warming potential (GWP)	None
	Depletion potential of the stratospheric ozone layer (ODP)	None
	Potential incidence of disease due to PM emissions (PM)	None
	Acidification potential, Accumulated Exceedance (AP)	None
	Eutrophication potential, Fraction of nutrients reaching marine end compartment (EP-marine)	None
ILCD type / level 2	Eutrophication potential, Accumulated Exceedance (EP-terrestrial)	None
	Formation potential of tropospheric ozone (POCP)	None
	Potential Human exposure efficiency relative to U235 (IRP)	1
ILCD type / level 3	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2
	Abiotic depletion potential for fossil resources (ADP-fossil)	2
	Water (user) deprivation potential, deprivation-weighted water consumption (WDP)	2
	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2
	Potential Comparative Toxic Unit for humans (HTP-c)	2
	Potential Comparative Toxic Unit for humans (HTP-nc)	2

Potential Soil quality index (SQP)	2
<p>Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.</p> <p>Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator</p>	

Resource use

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
RPEE	MJ	6,81E+00	4,98E-03	8,13E-01	1,07E-01	2,41E-03	0	5,98E-02	-2,16E-01
RPEM	MJ	7,04E-01	0,00E+00	-6,72E-01	0,00E+00	0,00E+00	0	-3,25E-02	0,00E+00
TPE	MJ	7,51E+00	4,98E-03	1,42E-01	1,07E-01	2,41E-03	0	2,73E-02	-2,16E-01
NRPE	MJ	1,57E+00	8,78E-02	6,82E-01	1,92E-01	4,25E-02	0	1,44E+00	-7,85E-01
NRPM	MJ	1,86E+00	0,00E+00	-6,10E-01	0,00E+00	0,00E+00	0	-1,26E+00	0,00E+00
TRPE	MJ	3,43E+00	8,78E-02	7,26E-02	1,92E-01	4,25E-02	0	1,82E-01	-7,85E-01
SM	kg	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
W	m ³	1,86E-02	5,63E-06	6,53E-04	1,02E-04	2,73E-06	0	4,62E-05	-2,08E-04

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non-renewable primary energy resources used as energy carrier; NRPM Non-renewable primary energy resources used as materials; TRPE Total use of non-renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non-renewable secondary fuels; W Use of net fresh water

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

End of life - Waste

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HW	kg	5,34E-07	4,21E-13	1,07E-08	1,66E-11	2,04E-13	0	9,35E-12	-1,06E-10
NHW	kg	2,61E-01	1,26E-05	2,46E-02	1,45E-04	6,09E-06	0	9,31E-01	-3,97E-04
RW	kg	4,47E-05	1,08E-07	2,37E-06	3,07E-05	5,24E-08	0	2,03E-06	-6,20E-05

HW Hazardous waste disposed; NHW Non-hazardous waste disposed; RW Radioactive waste disposed

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

End of life – output flow

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
CR	kg	0	0	0	0	0	0	0	0
MR	kg	0	0	0	0	0	0	0	0
MER	kg	0	0	5,61E-02	0	0	0	0	0
EEE	MJ	0	0	0	0	0	0	0	0
ETE	MJ	0	0	0	0	0	0	0	0

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

Information describing the biogenic carbon content at the factory gate

Biogenic carbon content	Unit	Value
Biogenic carbon content in product	kg C	0
Biogenic carbon content in the accompanying packaging	kg C	1,03E-02

Additional requirements

Location based electricity mix from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (foreground/core) per functional unit.

National electricity grid	Foreground / core (kWh)	GWP ^{total} (kg CO ₂ - eq/kWh)	SUM (kgCO ₂ - eq)
Electricity grid mix, Finland	1,53E+00	2,19E-01	3,34E-01

Guarantees of origin from the use of electricity in the manufacturing phase

The guarantee of origin utilized in this EPD is provided by Statkraft for hydropower. As 100% of the electricity consumption is covered with GoO, no residual mix calculation has been made.

Electricity source	Foreground / core (kWh)	GWP ^{total} (kg CO ₂ - eq/kWh)	SUM (kgCO ₂ - eq)
Amount of guarantee of origin electricity used in the foreground (Electricity, Hydropower, Finland)	1,53E+00	1,43E-02	2,18E-02
Amount of residual mix electricity used in the foreground	0	-	0

Additional environmental impact indicators required in NPCR Part A for construction products

In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-IOBC	kg CO ₂ eq.	3,50E-01	6,55E-03	5,51E-02	1,06E-02	3,22E-03	0	1,39E-02	-4,61E-02

GWP-IOBC Global warming potential calculated according to the principle of instantaneous oxidation.

Hazardous substances

The declaration is based upon reference to threshold values and/or test results and/or material safety data sheets provided to EPD verifiers. Documentation available upon request to EPD owner.

- The product contains no substances given by the REACH Candidate list or the Norwegian priority list.
- The product contains substances given by the REACH Candidate list or the Norwegian priority list that are less than 0,1 % by weight.
- The product contains dangerous substances, more then 0,1% by weight, given by the REACH Candidate List or the Norwegian Priority list, see table.
- The product contains no substances given by the REACH Candidate list or the Norwegian priority list. The product is classified as hazardous waste (Avfallsforskiten, Annex III), see table.

Indoor environment

The products covered by this EPD meets the legal requirements for stone wool thermal insulation.

Carbon footprint

Carbon footprint has not been worked out for the product.

Bibliography

ISO 14025:2010	Environmental labels and declarations - Type III environmental declarations - Principles and procedures
ISO 14044:2006	Environmental management - Life cycle assessment - Requirements and guidelines
ISO 21930:2007	Sustainability in building construction - Environmental declaration of building products
ISO 14040	EN ISO 14040:2009-11 Environmental management - Life cycle assessment - Principles and framework
EN 15804:2012+A2:2019	Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products
EN 12939:2000	Thermal performance of building materials and products – Determination of thermal resistance by means of guarded hot plate and heat flow meter methods – Products of high and medium thermal resistance
EN 12667:2001	Thermal performance of building materials and products – determination of thermal resistance by means of guarded hot plate and heat flow meter methods – products of high and medium thermal resistance
EN 13501-1:2007+A1:2009	Fire classification of construction products and building elements – part 1: Classification using data from reaction to fire tests
PCR	NPCR PART A Construction Products and Services
PCR	NPCR 012 Part B for Thermal Insulation Products.
CPR	Regulation (EU) No 305/2011 of the European parliament and of the council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC
CEN/TR 15941	Sustainability of construction works – Environmental product declarations – Methodology for selection and use of generic data; CEN/TR 15941:2010
DYNEA 2022	LCA results for 3 different binder data, results according EN 15884+A2, 2022
GaBi ts	GaBi ts dataset documentation for the software-system and databases, LBP, University of Stuttgart and Sphera, Leinfelden-Echterdingen, 2022 (https://www.gabi-software.com/support/gabi)
GHG 2022	Greenhouse gas conversion factors, https://www.gov.uk/government/publications/greenhouse-gas-reporting-conversion-factors-2022
Singh P, Goymann M, Goerke J	Background report for EPD of Paroc Stone Wool Insulation, January 2023.

	Program Operator	tlf	+47 23 08 80 00
	The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo Norway	e- post:	post@epd-norge.no
		web	www.epd-norge.no
	Publisher	tlf	+47 23 08 80 00
	The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo Norway	e- post:	post@epd-norge.no
		web	www.epd-norge.no
	Owner of the declaration	tlf	+358 46 876 8000
	Paroc Group Oy FI-00181, Helsinki, Finland	e- post:	InsulationEurope.Sustainability@owenscorning.com
		web	www.paroc.com
	Author of the life cycle assessment	tlf	+49 711 34 18 17-25
	Sphera Solutions GmbH Singh P, Goymann M, Goerke J	e- post:	info@sphera.com
		web	www.sphera.com
	ECO Platform ECO Portal	web	www.eco-platform.org
		web	ECO Portal

EPD for the best environmental decision



Global
Program
Operator