

NOBLE

WOOD - PRODUCT DATASHEET 2023



TECHNICAL DATA (EN 13489)		16 mm
Reaction to fire	EN 14342 Table 1	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Protoco Lacquer <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	4000
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥ 17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,132 0,152 0,172
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,121
Construction: softwood veneer and lamella core		4-layer

INSTALLATION		
Installation method	2-lock for floating or glue down	
Installation instruction	Download from www.tarkett.com Contact your supplier for more details	
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating underfloor heating system		Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²		

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Tarkoclean for hardwax oiled or lacquered floors Refresher for hardwax oiled or lacquered floors
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
These Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Hanaskog 2023.04



2-LOCK



91%
RENEWABLE
RESOURCES



www.realwood.eu



3029 0026
For floors with
Protoco Hardwax Oil



Tarkett

NOBLE

WOOD - PRODUCT DATASHEET 2023

DESIGN

A timeless floor inspired by the classic modular technique from the 1950s. This revisited design offers a contemporary look thanks to a surface brushing that allows the light to reflect on the surface in new and exciting ways. Each squared lamella is applied by hand, to create a block pattern, on top of Tarkett's engineered and layered construction. The random combination of nuances in the colour of natural oak allows every installer to compose stunning visual patterns, that will change depending on the installation and the incoming light. Thanks to this wonderful handcrafted work with alternating grain directions, colour variations and twisted designs, every floor becomes a unique and exclusive creation. We like to call it "perfect imperfection".

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel	Character	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Noble Oak Scandinavia	7806008	2 028 x 192 x 16	Basket Weave	Proteco Hardwax Oil	Brushed	-	Lively	1	0190-0123	3,5	6	2,34	81,9	9,0
Noble Oak Manhattan	7806014	2 280 x 190 x 16	Small Block	Proteco Hardwax Oil	Brushed	-	Lively	1	0190-0123	3,5	6	2,60	91,0	9,0
Noble Oak Brooklyn	7806903	2 280 x 190 x 16	Big Block	Proteco Hardwax Oil	Brushed	-	Calm	1	0190-0123	3,5	6	2,60	91,0	9,0
Noble Oak Art Deco	7806009	2 028 x 192 x 16	Basket Weave	Proteco Hardwax Oil	Brushed	-	Lively	1	0190-0123	3,5	6	2,34	81,9	9,0
Noble Oak Soho	7806012	2 280 x 190 x 16	Big Block	Proteco Hardwax Oil	Brushed	-	Calm	1	0190-0123	3,5	6	2,60	91,0	9,0
Noble Oak Retro	7806007	2 028 x 192 x 16	Basket Weave	Proteco Lacquer	-	-	Lively	1	0190-0123	3,5	6	2,34	81,9	9,0
Noble Oak Classic	7806018	2 028 x 192 x 16	Basket Weave	Proteco Natura	Brushed	-	Lively	1	0190-0123	3,5	6	2,34	81,9	9,0
Noble Oak Wasa	7806010	2 028 x 192 x 16	Basket Weave	Proteco Hardwax Oil	Brushed	-	Lively	1	0190-0123	3,5	6	2,34	81,9	9,0
Noble Oak Chelsea	7806016	2 280 x 190 x 16	Small Block	Proteco Hardwax Oil	Brushed	-	Lively	1	0190-0123	3,5	6	2,60	91,0	9,0
Noble Oak Bronx	7806017	2 280 x 190 x 16	Big Block	Proteco Hardwax Oil	Brushed	-	Lively	1	0190-0123	3,5	6	2,60	91,0	9,0

Due to the nature of the material this table shows typical values.

1: Quercus Robur & Quercus Petraea




Noble Oak Scandinavia



Noble Oak Manhattan



Noble Oak Brooklyn




Noble Oak Art Deco



Noble Oak Soho



Noble Oak Retro



Noble Oak Classic



Noble Oak Wasa



Noble Oak Chelsea



Noble Oak Bronx

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com

